

Erweiterungsfedern UNI-X, RSN

Verzinktstahl Material:

Einheit: Stuck Verpackung:

Wird mit dem UNI-X, RSN-Schienensystem Beschreibung:

verwendet

| HIGHT [mm] | WIDTH [mm] | | | | | | | | | | | |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|--|
| | 2250 | 2375 | 2400 | 2500 | 2600 | 2750 | 3000 | 3250 | 3500 | 3750 | | |
| 2000 | SN215 | SN216 | SN216 | SN217 | SN217 | SN217 | SN218 | SN219 | SN220 | SN220 | | |
| 2125 | SN415 | SN416 | SN416 | SN417 | SN417 | SN417 | SN418 | SN419 | SN420 | SN420 | | |
| 2250 | SN415 | SN416 | SN416 | SN417 | SN417 | SN417 | SN418 | SN419 | SN420 | SN420 | | |
| 2375 | SN615 | SN616 | SN616 | SN617 | SN617 | SN617 | SN618 | SN619 | SN620 | SN620 | | |
| 2500 | SN615 | SN616 | SN616 | SN617 | SN617 | SN617 | SN618 | SN619 | SN620 | SN620 | | |

| HIGHT [mm] | WEIGHT [kg] | | | | | | | | | |
|------------|-------------|---------|---------|---------|---------|----------|--|--|--|--|
| 2000 | 47-53kg | 54-58kg | 59-64kg | 65-70kg | 71-76kg | 77-85kg | | | | |
| | SN215 | SN216 | SN217 | SN218 | SN19 | SN220 | | | | |
| 2125 | 51-56kg | 57-62kg | 62-68kg | 69-73kg | 74-81kg | 82-89kg | | | | |
| | SN415 | SN416 | SN417 | SN418 | SN419 | SN420 | | | | |
| 2250 | 53-59kg | 60-64kg | 65-71kg | 72-77kg | 78-85kg | 86-94kg | | | | |
| | SN415 | SN416 | SN417 | SN418 | SN419 | SN420 | | | | |
| 2375 | 56-63kg | 64-69kg | 70-75kg | 76-82kg | 83-90kg | 91-98kg | | | | |
| | SN615 | SN616 | SN617 | SN618 | SN619 | SN620 | | | | |
| 2500 | 59-66kg | 67-72kg | 73-78kg | 79-86kg | 87-94kg | 95-103kg | | | | |
| | SN615 | SN616 | SN617 | SN618 | SN619 | SN620 | | | | |

