

Пружины растяжения UNI-X, RSN

Материал: оцинкованная сталь

Единица: 1 шт

Торговое количество: 1

Описание: Используется с системой направляющих UNI-X, RSN

HIGHT [mm]	WIDTH [mm]									
	2250	2375	2400	2500	2600	2750	3000	3250	3500	3750
2000	SN215	SN216	SN216	SN217	SN217	SN217	SN218	SN219	SN220	SN220
2125	SN415	SN416	SN416	SN417	SN417	SN417	SN418	SN419	SN420	SN420
2250	SN415	SN416	SN416	SN417	SN417	SN417	SN418	SN419	SN420	SN420
2375	SN615	SN616	SN616	SN617	SN617	SN617	SN618	SN619	SN620	SN620
2500	SN615	SN616	SN616	SN617	SN617	SN617	SN618	SN619	SN620	SN620

HIGHT [mm]	WEIGHT [kg]									
	2250	2375	2400	2500	2600	2750	3000	3250	3500	3750
2000	47-53kg SN215	54-58kg SN216	59-64kg SN217	65-70kg SN218	71-76kg SN219	77-85kg SN220				
2125	51-56kg SN415	57-62kg SN416	62-68kg SN417	69-73kg SN418	74-81kg SN419	82-89kg SN420				
2250	53-59kg SN415	60-64kg SN416	65-71kg SN417	72-77kg SN418	78-85kg SN419	86-94kg SN420				
2375	56-63kg SN615	64-69kg SN616	70-75kg SN617	76-82kg SN618	83-90kg SN619	91-98kg SN620				
2500	59-66kg SN615	67-72kg SN616	73-78kg SN617	79-86kg SN618	87-94kg SN619	95-103kg SN620				

